

Technical data sheet

	Wörth		Zorbau		
Corrugator width	3.350 mm		2.800 mm		
Minimum order quantity standard quality	200 QM orders with quantities of less than 200 qm, the amount will be increased to the minimum quantity automatically.				
special quality products open corrugated cardboard standard quality	7000 QM 4000 QM				
special quality products open corrugated cardboard	E/B/C/EE/EB/BC/AC/AAC G/F/GE/FE/FB/FC/BB/EC/AA/EBE/ECE GE/FE/EE/EB				
Stack height (including pallet)	min.	1.200 mm			
	max.	2.000 mm			
Palletising with equal quantities can not usually be realised					
Format size (in mm)		width	chop length	width	chop length
one-/twocorrugated	min.	280	500	280	550
AC und AAC	min.	350	800	-	-
aforementioned wave types	max.	2.450	5.500	2.400	4.000
aforementioned wave types or	max.	3.310	2.450	2.760	2.400
minimum pallet height 500 mm					
Number of flutes available	max. 30 3-Point-Profile		max. 42 3-Point-Profile		
Creasing clearance	2 distance of flute a row min. 57 mm		1. on 3. flutes min. 72 mm		
Creasing profile	3-Point, 5-Point and head on flat		3-Point		
Measure precision:					
length	+/- 1mm pro Meter				
width	+/- 2mm				
scores	+/- 2mm				
Palletising	DB-Euro-Palette 1200x800x144 mm immediate exchange one way pallets 1200x800x130 mm Sonderpaletten auf Anfrage (nur Zorbau)				
Strapping	third party logistics partner (via truck)				
Formats with tear strip	yes		no		
Certificates					
DIN EN ISO 9001: 2008	yes		no		
DIN EN ISO 22000	yes		no		
DIN EN ISO 14001	yes		no		
OHSAS 18001	yes		no		
DIN EN ISO 50001: 2011	yes		yes		
FSC	yes		yes		



Important notice:

Differences between delivery note and actual delivered quantity of 1 % are due to technical restraints and are therefore not liable to refunds.

Furthermore, the top and bottom formats on a pallet of each pile are accounted for in quantity and price.

In case of changes in the raw material market or for logistical reasons Eurowell reserves the right to produce a different but comparable paper composition.

This procedure is based on compliance with technical specs and requirements of our standard grades, surface weight or single paper weight may vary.

Our corrugated board formats are suitable for dry, non-greasing food. However, we recommend that food shall only be packed with a suitable intermediate packaging.

To guarantee a good processing quality, we recommend the following conditions for storage:
Temperature approx. 23 degrees and air-humidity of approx. 50 %

As of 02/2019